

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/009680 A3

(51) International Patent Classification⁷: **G01N 3/08**,
3/10, 11/00

(21) International Application Number:
PCT/US2004/023116

(22) International Filing Date: 20 July 2004 (20.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/489,111 23 July 2003 (23.07.2003) US

(71) Applicant (for all designated States except US): **ENGIS CORPORATION** [US/US]; 105 W. Hintz Road, Wheeling, IL 60090 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BENEA, Ion**

[RO/US]; 575 Denoyer Trail, Wheeling, IL 60090 (US). **GRIFFIN, Stephen** [US/US]; 61 Grange Road, Elk Grove Village, IL (US). **DOYLE, Ralph** [US/US]; 639 North Hawk Street, Palatine, IL 60067 (US).


(74) Agents: **MESSINA, Michael, A.** et al.; McDermott Will & Emery LLP, 600 13th Street, N.W., Washington, DC 20005-3096 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: APPARATUS FOR MEASURING THE CRUSHING STRENGTH OF MICRON SUPERABRASIVES



(57) Abstract: A method and apparatus are provided for measuring the crushing strength of an abrasive, comprising particles, used in a lapping process. Embodiments include a crushing strength tester having a cup (115) for holding the abrasive; a first motor (135) for rotating the cup in a first direction; a piston (120) having a face for rotatably fitting within the cup and contacting the abrasive; a second motor (140) for rotating the piston in a second direction opposite the first direction; and press for pressing the piston against the abrasive and crushing the particles while the first and second motors are rotating. An initial particle size distribution for the particle is determined, then the abrasive is subjected to a crushing force approximately equal to that of the lapping process using the crushing force approximately equal to that of the lapping process using the crushing strength tester. A post-crushing particle size distribution for the particles is determined, and the initial and post-crushing particle size distributions are compared.



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report:

21 July 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report